

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

**Claim 1 (canceled)**

1           **Claim 2 (currently amended):**     An image forming  
2     apparatus ~~according to claim 1, comprising:~~  
3           a photosensitive member which is rotatably disposed,  
4     and on which an electrostatic latent image is developed to  
5     form a toner image;  
6           a cleaning blade which comprises a body portion  
7     configured by an elastic plate member, and a base plate  
8     portion supporting said body portion, and which removes  
9     away a toner that remains on said photosensitive member  
10    after the toner image is transferred, by means of said body  
11    portion that pressingly contacts said photosensitive  
12    member;  
13          a housing which holds said photosensitive member and  
14    said cleaning blade; and  
15          a recess which is disposed in said housing, and which  
16    accommodates at least part of said base plate,  
17    wherein said cleaning blade being pressingly secured  
18    to said recess by said photosensitive member,

19            wherein said recess which is disposed in said housing  
20       has first and second projections which butt against said  
21       base plate portion.

1            **Claim 3 (original):**    An image forming apparatus  
2       according to claim 2, wherein said base plate portion has  
3       first and second end portions in a direction which is  
4       parallel to a rotation axis of said photosensitive member,  
5            said housing has first and second recesses which are  
6       opposed to said first and second end portions of said base  
7       plate portion, respectively,

8            each of said first and second recesses has said first  
9       and second projections,

10           said first end portion of said base plate portion  
11       butts against said first and second projections of said  
12       first recess, and

13           said second end portion of said base plate portion  
14       butts against said first and second projections of said  
15       second recess.

1            **Claim 4 (currently amended):**    An image forming  
2       apparatus ~~according to claim 1,~~ comprising:  
3       \_\_\_\_\_ a photosensitive member which is rotatably disposed,  
4       and on which an electrostatic latent image is developed to  
5       form a toner image;

6     a cleaning blade which comprises a body portion  
7     configured by an elastic plate member, and a base plate  
8     portion supporting said body portion, and which removes  
9     away a toner that remains on said photosensitive member  
10    after the toner image is transferred, by means of said body  
11    portion that pressingly contacts said photosensitive  
12    member;  
13    a housing which holds said photosensitive member and  
14    said cleaning blade; and  
15    a recess which is disposed in said housing, and which  
16    accommodates at least part of said base plate,  
17    wherein said cleaning blade being pressingly secured  
18    to said recess by said photosensitive member,  
19       wherein part of said base plate portion is pressed  
20    against a bottom of said recess.

1       **Claim 5 (original):**   An image forming apparatus  
2    according to claim 4, wherein said cleaning blade is  
3    secured to said housing by said photosensitive member, said  
4    first and second projections, and said bottom of said  
5    recess.

1       **Claim 6 (original):**   An image forming apparatus  
2    according to claim 2, wherein said recess has said bottom,  
3    a first wall which is positioned in front of said bottom in  
4    a rotation direction of said photosensitive member, and a

5 second wall which is positioned in rear of said bottom in  
6 the rotation direction of said photosensitive member,

7 said first projection is disposed on said first wall  
8 with being separated from said bottom by a predetermined  
9 distance, and

10 said second projection is disposed on said second wall  
11 with being separated from said bottom by a distance which  
12 is larger than said predetermined distance.

1 **Claim 7 (original):** An image forming apparatus  
2 according to claim 2, wherein longitudinal directions of  
3 said first and second projections are parallel to a  
4 rotation axis of said photosensitive member.

1 **Claim 8 (currently amended):** An image forming  
2 apparatus ~~according to claim 1, comprising:~~  
3 a photosensitive member which is rotatably disposed,  
4 and on which an electrostatic latent image is developed to  
5 form a toner image;  
6 a cleaning blade which comprises a body portion  
7 configured by an elastic plate member, and a base plate  
8 portion supporting said body portion, and which removes  
9 away a toner that remains on said photosensitive member  
10 after the toner image is transferred, by means of said body  
11 portion that pressingly contacts said photosensitive  
12 member;

13        a housing which holds said photosensitive member and  
14        said cleaning blade; and  
15        a recess which is disposed in said housing, and which  
16        accommodates at least part of said base plate,  
17        wherein said cleaning blade being pressingly secured  
18        to said recess by said photosensitive member,  
19        wherein a hook which prevents said cleaning blade from  
20        slipping off said housing is disposed on said housing.

1           **Claim 9 (original):**    An image forming apparatus  
2        according to claim 8, wherein an engagement portion which  
3        is to be engaged with said hook is disposed in said base  
4        plate portion of said cleaning blade.

1           **Claim 10 (original):**    An image forming apparatus  
2        according to claim 8, wherein said hook is disposed in a  
3        vicinity of each of said first and second end portions of  
4        said base plate.

1           **Claim 11 (original):**    An image forming apparatus  
2        according to claim 3, wherein part of said base plate  
3        portion is pressed against a bottom of said recess.

1           **Claim 12 (original):**    An image forming apparatus  
2        according to claim 3, wherein said recess has said bottom,  
3        a first wall which is positioned in front of said bottom in

4 a rotation direction of said photosensitive member, and a  
5 second wall which is positioned in rear of said bottom in  
6 the rotation direction of said photosensitive member,

7 said first projection is disposed on said first wall  
8 with being separated from said bottom by a predetermined  
9 distance, and

10 said second projection is disposed on said second wall  
11 with being separated from said bottom by a distance which  
12 is larger than said predetermined distance.

1 **Claim 13 (original):** An image forming apparatus  
2 according to claim 12, wherein a hook which prevents said  
3 cleaning blade from slipping off said housing is disposed  
4 on said housing.

1 **Claim 14 (original):** An image forming apparatus  
2 according to claim 3, wherein longitudinal directions of  
3 said first and second projections are parallel to a  
4 rotation axis of said photosensitive member.

1 **Claim 15 (original):** An image forming apparatus  
2 according to claim 3, wherein a hook which prevents said  
3 cleaning blade from slipping off said housing is disposed  
4 on said housing.

1           **Claim 16 (original):**    An image forming apparatus  
2   according to claim 5, wherein a hook which prevents said  
3   cleaning blade from slipping off said housing is disposed  
4   on said housing.

1           **Claim 17 (original):**    An image forming apparatus  
2   according to claim 6, wherein a hook which prevents said  
3   cleaning blade from slipping off said housing is disposed  
4   on said housing.

1           **Claim 18 (original):**    An image forming apparatus  
2   according to claim 7, wherein a hook which prevents said  
3   cleaning blade from slipping off said housing is disposed  
4   on said housing.

1           **Claim 19 (original):**    An image forming apparatus  
2   according to claim 14, wherein a hook which prevents said  
3   cleaning blade from slipping off said housing is disposed  
4   on said housing.

1           **Claim 20 (original):**    An image forming apparatus  
2   according to claim 15, wherein an engagement portion which  
3   is to be engaged with said hook is disposed in said base  
4   plate portion of said cleaning blade.